



# FUSION



## SPECIFICATIONS

- 5,500 lb Self-Loading Wheel Lift
- 8,000 lb Tow Rating
- 25 Degree Negative & Positive Tilt
- Recovery Boom at Boom Head Swivel 10,000 lbs
- 8,000 lb Planetary Winch
- Recovery Boom
- 80" Wheel Lift Reach

All Ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Dynamic Towing reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.

## STANDARD FEATURES

- 60" Cab To Axel Steel Modular Body
- 45 Cubic Feet of Available Storage
- 2 Large Top Loading Tool Compartments
- 2 Large Side Loading Compartments
- Self Centering Cross Bar
- Wheel Spacers

## CHASSIS RECOMMENDATIONS

- |                               |            |
|-------------------------------|------------|
| Minimum Cab to Axel           | 60"        |
| Max. Cab to Axel Tunnel Boxes | 108"       |
| Suggested GVWR                | 14,500 lbs |



LIKE US ON FACEBOOK



[WWW.DYNAMICTOW.COM](http://WWW.DYNAMICTOW.COM)

CONTACT US: 1-800-831-9299