



755-SERIES



4 YEAR WARRANTY



SPECIFICATIONS

- 5,500 lb Self-Loading Wheel Lift
- 8,000 lb Tow Rating
- 25 Degree Negative & Positive Tilt
- Recovery Boom at Boom Head Swivel 10,000 lbs
- 8,000 lb Planetary Winch
- Recovery Boom
- 80" Wheel Lift Reach

All Ratings are based on structural factors only, not vehicle capacities or capabilities. Specifications shown are approximations and may vary depending on chassis selected. Dynamic Towing reserves the right to change or modify product and or specifications without notice or obligation. Some equipment shown is optional.



STANDARD FEATURES

- 60" One Piece Steel Body
- Lightning Body
- 2 Large Top Loading Compartments
- Self Centering Cross Bar
- Wheel Spacers

OPTIONAL FEATURES

- Twin Line Recovery Boom
- 8,000 lb Drag Winch
- Stainless Steel Pylon
- Diamond Plate Dress Up Package
- Side Load Tool Boxes
- Motorcycle Attachment

CHASSIS RECOMMENDATIONS

- Minimum Cab to Axel 60"
- Max. Cab to Axel Tunnel Box 108"
- Suggested GVWR 14,500 lbs

LIKE US ON FACEBOOK



WWW.DYNAMICTOW.COM

CONTACT US: 1-800-831-9299